

Mainfix ECO MEVB



Mainfix ECO

Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	UL94 V2-

metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVB07M12B	M12	07	35,0	12,0	50
MEVB10M16B	M16	10	37,0	12,0	50
MEVB12M16B	M16	12	39,5	12,0	50
MEVB14M20B	M20	14	42,0	13,0	50
MEVB17M20B	M20	17	45,0	13,0	50
MEVB17M25B	M25	17	45,0	13,0	50
MEVB23M25B	M25	23	37,0	13,0	25
MEVB23M32B	M32	23	37,0	13,0	25
MEVB29M32B	M32	29	44,0	15,0	25
MEVB29M40B	M40	29	44,0	15,0	25
MEVB36M40B	M40	36	52,0	15,0	10
MEVB36M50B	M50	36	52,0	15,0	10
MEVB48M50B	M50	48	64,0	16,0	5
MEVB48M63B	M63	48	64,0	16,0	5



90° Bogen-Wellrohrverschraubung mit metrischem Kunststoff-Außengewinde.

90° elbow polyamide fitting with metric polyamide male thread.

Mainfix ECO MEV



Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Nitril Gummi nitrile rubber
Temperatur temperature	-40°C - +120°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW 1 tube DN 1	Wellrohr NW 1 tube DN 1	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEV07B	-	07	07	33,5	20
MEV10B	-	10	10	36,5	10
MEV12B	-	12	12	44,5	10
MEV14B	-	14	14	48,0	10
MEV17B	-	17	17	46,0	10
MEV23B	-	23	23	46,0	10
MEV2329B	-	23	29	48,0	10
MEV29B	-	29	29	48,0	10
MEV36B	-	36	36	60,0	10
MEV48B	-	48	48	70,0	5

Wellrohrverbinder

corrugated tube connector

